



MID RACING TR50



Tarmac Black(TBK) (17×9.0J)



Tarmac Black(TBK) (17×7.5J)



Tarmac Black(TBK) (15×7.0J)

Flat-surfaced sports royal 5-spoke

○ Spec

Product Name	TR50
Size	15inch / 16inch / 17inch / 18inch
Construction Method	Cast flow-formed 1-piece wheel (15-inch and 16-inch wheels are cast 1-piece wheels) 1570 +35 4-100 / 1670 +35 4-100 / 1775 +40 5-100 / 1775 +48 5-114.3 / 1790 +22 5-114.3 The above sizes are manufactured in Thailand (all others are made in China).
Safety Standards	JWL VIA compliant (6H-139.7 is JWL (800KG) JWL-T (955KG), 5H-139.7 is JWL (620KG) JWL-T (700KG) VIA compliant)
Color	Tarmac Black (TBK)
Included	Center cap (except 5-139.7 size), Air valve (Black) , Sticker NO.2 MID_Wheels_valve_BLK 57003
Optional	Center cap ¥ 3,000 Air valve (Black) ¥ 800

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	INSET (): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (φ)	DRILL (φ)	PRICE	DISK PROTRUSIO N (mm)	Load (kg)	Load (lbs)
						TBK			
15x5J	45(35)	4	100	67.1	29-13	31,000	10.6	500	1102.31
15x7J	35(35)	4	100	67.1	29-13	34,000	-	500	1102.31
16x6J	45(42)	4	100	67.1	29-13	38,000	5.8	530	1168.44
16x7J	35(35)	4	100	67.1	29-13	40,000	-	530	1168.44
17x7.5J	40(51)	5	100	67.1	29-13	46,000	-	540	1190.49
	48(43)		114.3	73.1				690	1521.18
17x9J	22(38)	5	114.3	73.1	29-13	49,000	-	690	1521.18
18x8J	45(43)	5	114.3	73.1	29-13	50,500	-	690	1521.18
18x8.5J	45(35)	5	100	67.1	29-13	51,000	-	540	1190.49
			120	72.6	29-15			720	1587.32
18x9.5J	12(54)	5	114.3	73.1	29-13	53,000	-	690	1521.18

Caution

TPMS compatible

This product has the disk protruding beyond the rim depending on the size, so please take care when installing