MID WHEELS GriD

Precision in Every Spoke.

Metallic Gray
19x7.5J+45 5-120

Metallic Gray
15x4.5J+45 4-100

Metallic Gray
13x4.0J+43 4-100

Spec

Product Name	GriD
Size	12inch /13inch / 14inch /15inch / 16inch /17inch /18inch / 19inch
Construction Method	Cast 1pc. Wheel Made in China
Safety Standards	Complies with JWL, JWL-T (12×3.50B / 13×4.00B / 13×4.50B), and VIA standards.
Color	Metallic Gray
Included	Center cap, valve
Optional	Center cap ¥3,000 (ex. tax), valve ¥400 (ex. tax)

The photo is a representative image. Please visit our website for other types of product images

Prices are noted in Japanese YEN(JPY). Specifications in the English version are intended for customers outside of Japan and do not include Japan sales tax.

SIZE	INSET ( ): HUB CLEARANCE (mm)	HOLE	P.C.D.	HUB BORE (Φ)	DRILL (Φ)	PRICE	Load (kg)	Load (lbs)
						MGR		
12x3.5B	42(35)	4	100	67.1	32-13	15,500	360	793.66
13x4J	43(33)	4	100	67.1	32-13	16,500	500	1102.31
13x4.5J	50(28)	4	100	67.1	32-13	17,000	500	1102.31
14x4.5J	45(33) 50(28)	4	100	67.1	32-13	18,500	500	1102.31
14x5.5J	38(42) 45(35)	4	100	67.1	32-13	19,500	500	1102.31
15x4.5J	45(33)	4	100	67.1	32-13	20,500	500	1102.31
15x5.5J	43(42) 50(35)	4	100	67.1	32-13	21,500	500	1102.31

15x6J	44(44)	5	100	54.1	35-19	22,000	505	1113.33
	45(43)			67.1	32-13			
	52(36)		114.3	73.1			690	1521.19
16x6J	43(42)	4	100	67.1	32-13	25,500	530	1168.45
	50(35)							
	40(45)	5						
16x6.5J	48(43)	5	100	67.1	32-13	26,000	530	1168.45
	38(53)		114.3	73.1			690	1521.19
	48(43)							
	53(38)							
17x6J	40(42)	4	100	67.1	32-15	29,500	530	1168.45
		5					540	1190.49
17x6.5J	▲40(35)	5	120	60.1	38-22.5	30,000	720	1587.33

17x7J	48(45)	5	100	67.1	32-13	30,500	540	1190.49
	▲37(56)		114.3	60.1	35-19		690	1521.19
	38(55)			73.1	32-15			
	■40(53)			60.1	33-15			
	▲47(46)				35-19			
	48(45)			73.1	32-15			
	55(38)							
18x7J	■39(52)	5	114.3	60.1	33-15	35,000	690	1521.19
	48(43)			73.1	32-15			
	▲40(51)		120	60.1	38-22.5		720	1587.33
18x7.5J	■35(57)	5	114.3	60.1	33-15	36,000	690	1521.19
	▲37(57)				35-19			
	38(56)			73.1	32-15			
	53(43)							

19x7.5J	38(53)	5	114.3	73.1	32-15	48,000	690	1521.19
	■41(50)			60.1	33-15			
	48(43)			73.1	32-15			
	▲40(51)		120	60.1	38-22.5		720	1587.33
19x8J	■25(35)	5	120	60.1	33-15	49,000	720	1587.33

Caution
▲: For Toyota flat-seat nuts only. Hub-centric design.
■: For vehicles with M14×1.5 bolts with 14R spherical seats only. Hub-centric design.